

# **TC75 Series Rugged Touch Computer**

### YOUR FRONT LINE TO A SMARTER ENTERPRISE

Your field workforce needs a mobile computer to access the people and information required to maximize efficiency and better serve your customers. You want to give them an enterprise-class handheld built for life out in the field — yet your workers expect a device that is every bit as refined and easy-to-use as their own consumer smartphone. The TC75 Series is the Android<sup>™</sup> enterprise touch computer that delivers it all. A choice of Android OS, fortified for use in the enterprise. A rugged design that delivers reliable everyday operation. Anywhere anytime access to virtually any information in your back-end systems. The ability to capture more types of data faster than ever before. Instant push-to-talk communications with co-workers out in the field as well as supervisors, dispatch and more back in the office. 4G LTE support for a robust wireless connection on the world's fastest cellular networks. And a full complement of accessories meets the unique needs of virtually any mobile worker. The TC75 Series — the easy way to empower your field teams with a true mobile office.



TC75x

#### Mx — Making Android a More Robust Enterprise OS

Every TC75 Series ships with Mobility Extensions (Mx), a series of features that make Android a more robust enterpriseclass operating system. Mx minimizes IT support time and maximizes worker productivity and device uptime by providing better control of your mobile devices, application access and Wi-Fi performance and security. Standard Configuration TC75 and TC75x devices come with Google Mobile Services (GMS) which provides integrated Google applications such as Gmail and Google Maps. Professional Configuration TC75 and TC75x devices ship without GMS, removing GMS applications and services. Both configurations are based on Android Open Source (AOSP) and ship with respective Android Enterprise functionality.

#### World-class Data Capture

An integrated enterprise-class imager offers Zebra's proprietary PRZM Intelligent Imaging technology, a megapixel sensor and advanced optics, enabling the lightning-fast capture of 1D and 2D barcodes in virtually any condition. The rear-facing color camera enables the easy capture of highresolution photos, signatures, videos and more, so workers can capture more types of business intelligence to streamline more business processes. The front camera allows workers to place a video call to get the on-the-spot assistance they need. And Near Field Communications automates identity verification at facility entry points.

#### Maximum Data Entry Flexibility with an Industry Leading Dual Mode Touch Panel

Let your users choose their preferred data input pair: finger and gloved finger or finger and stylus — ideal for crisp signature capture. The intelligent 4.7 in. display automatically adjusts as needed, unlike competitive devices that require setting adjustments every time the user switches data input method.

#### Automatically Capture Data and Process Entire Documents

With SimulScan Document Capture, your workers can simultaneously capture barcodes, text fields, phone numbers, images, signatures and even check boxes in the time it takes to press a button, improving invoicing speed, order speed and more.

#### Superior Audio Quality and Functionality for a New Level of Voice Flexibility

Up to four times the loudness of popular smartphones and noise cancelling technology provides crystal clear audio on both ends of every call. Support for Workforce Connect Push-to-Talk (PTT) Express and Pro provides an instant connection to co-workers in the field, plus supervisors and other support staff back in the office.

#### Mobility DNA

mobile computers.

Every strand of your mobility platform is simpler with Zebra's Mobility DNA. That's because, from the start, you have the industry's most comprehensive suite of mobility must-haves to accelerate your solution. More off-the shelf end-user apps, more robust administration utilities and easier app development. Purpose built for the enterprise, Mobility DNA makes ease, confidence and value

#### PowerPrecision+ Battery for Best-In-ClassPower and Manageability<sup>1</sup>

intrinsic to your investment and our full line of Android

Your workers depend on their mobile devices nearly every minute of the workday. This user replaceable battery ensures that workers have plenty of power for the longest shift and devices are always available. A wealth of easily accessible battery metrics make it easier than ever to identify, remove and replace aging batteries. And with Warm Swap mode, it lets users change the battery without having to power down the device or close open apps

#### A Robust Accessory Family for Easy On-the-Go Device Management

Accessories include a flexible vehicle cradle for charging — even with snap-on accessories attached. A magnetic stripe reader enables mobile payment. The field attachable trigger handle brings comfort to scan intensive tasks. Select Zebra Bluetooth printers enable anywhere anytime printing. And backroom management is easier and more cost effective than ever thanks to our unique ShareCradle System that accommodates the TC75 Series and future Zebra devices.

#### Rugged and Ready for All-day Every Day Use Out in the Field

The TC75 Series delivers reliable operation, even after multiple 8 ft./2.4 m drops to concrete and 2,000 consecutive 3.2 ft./1 m tumbles in our punishing tumble test. With IP65 and IP67 sealing, the TC75 Series is dusttight and can survive complete immersion in water. And the Corning Gorilla Glass touch panel and scanner exit window bring a new level of durability to two of the most vulnerable components on any handheld device.

### THE TC75 SERIES — THE RIGHT DEVICE MAKES ALL THE DIFFERENCE.

For more information, visit www.zebra.com/tc75series or access our global contact directory at www.zebra.com/contact

#### Boost efficiency and customer service with the TC75 Series in:

#### T&L

- Proof of delivery
- Asset management
  Asset tracking
- Scheduling
- Routing
- Location services

#### Field Service

- Asset management
- Parts inventory
- InvoicingTask management
- Location based
- services
- Technical assistance
- Appointment scheduling
- Service automation

#### Direct Store Distribution (DSD)/ Route Accounting

- Order automation
- Delivery trackingInventory
- inventory management
- Store setup
- Customer support

#### Government and Public Safety

- Alternate to
- two-way radio
- Data collection
- Records query
- Real time data and voice
- ID validation/
- ticketing

  Location services
- Resource
   deployment
- Document on
- the scene video and photos

## **TC75 Series Specifications**

161 mm L x 84 mm W x 28 mm DD         Weight       13.3 oz./376 g         Display       4.7 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel         Imager Window       Corning Gorilla Glass         Touchpanel       Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass         Backlight       LED backlight         Power       Image Precision/ PowerPrecision/PowerPrecision+1: Improved battery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-Ion 3.7 V, 4620 mAh typical; battery swap function         Expansion Slot       TC75: User accessible MicroSD up to 32G8 SDHC and up to 64 GB SDXC TC75x: user accessible MicroSD up to 32G8 SDHC and up to 128 GB SDXC         SIM       TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF)         Network       USB 2.0 High Speed (host and client); WLAN         Connections       Audible tone; multi-color LEDs; vibration         Keypad       On-screen keypad; Enterprise Keyboard         Voice and Audio       Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice         PERFORMANCE CHARACTERISTICS       CPU       TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor         Operating System <td< th=""><th>Dimensions</th><th>6.3 in. L x 3.3 in. W x 1.1 in. D/</th></td<>	Dimensions	6.3 in. L x 3.3 in. W x 1.1 in. D/
Display       4.7 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel         Imager Window       Corning Gorilla Glass         Touchpanel       Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass         Backlight       LED backlight         Power       PowerPrecision/PowerPrecision+ <sup>1</sup> : Improved battery technology for advanced state of health and real-time visibility into battery metrics for better battery technology for advanced state of health and real-time visibile MicroSD up to 32GB SDHC and up to 64 GB SDXC         TC75: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC         TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF)         Network       USB 2.0 High Speed (host and client); WLAN         Connections       Audible tone; multi-color LEDs; vibration         Keypad       On-screen keypad; Enterprise Keyboard         Voice and Audio       Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice         PERFORMANCE CHARACTERISTICS       CPU       TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hax / 100 ugat) with Mx         Memory       TC75: 1.9 ENAM / 8 GB Flash pSLC or 4 GB RAM / 3 2 GB Flash pSLC       TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 3 2 GB Flash pSLC         USER ENVIRONMENT       Operating Temp.	Dimensions	
bright, outdoor viewable; optically bonded to touch panel         Imager Window       Corning Gorilla Glass         Touchpanel       Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass         Backlight       LED backlight         Power       Imager Window         Forware       Imager Window         Power       Imager Window         Corning Gorilla Glass       Backlight         Power       Imager Window         Corning Gorilla Glass       Backlight         Power       Imager Window         Cornocomposition       BowerPrecision/PowerPrecision+1: Improved         Dattery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery wap function         Retwork       C75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC         TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC       TC75x: USER accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC         Notification       Audible tone; multi-color LEDs; vibration         Keypad       On-screen keypad; Enterprise Keyboard         Voice and Audio       Three microphone support with noise cancellation; vibrate aler; speaker, Bluetooth wireless headset support, High quality speaker phone; PTT headset supoprit, Cellular circuit switch voice; HD Voice	Weight	13.3 oz./376 g
Touchpanel       Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass         Backlight       LED backlight         Power       PowerPrecision/PowerPrecision+!: Improved battery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-Ion 3.7 V, 4620 mAh typical; battery swap function         Expansion Slot       TC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC         TC75: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC       TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF)         Network       USB 2.0 High Speed (host and client); WLAN         Connections       Audible tone; multi-color LEDs; vibration         Keypad       On-screen keypad; Enterprise Keyboard         Voice and Audio       Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice         PERFORMANCE CHARACTERISTICS       CPU         CPU       TC75: 1.6 B RAM / 8 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC         USER ENVIRONMENT       Operating 7H-20° C to 50°C         Operating Temp.       -4° F to 152° F/-20° C to 50°C         Storage Temp.       -4° F to 158° F/-40° C to 70° C         Humidity       5% to 85% non-condensing         Drop Specification       Multiple 8	Display	bright, outdoor viewable; optically bonded to
or gloved fingertip input (conductive stylus sold separately); Corning Gorilla GlassBacklightLED backlightPowerPowerPrecision/PowerPrecision/PowerPrecision+! Improved battery technology for advanced state of health and real-time visbility into battery metrics for better battery management LI-Ion 3.7 V, 4620 mAh typical; battery swap functionExpansion SlotTC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXCSIMTC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF)Network ConnectionsUSB 2.0 High Speed (host and client); WLAN ConnectionsNotificationAudible tone; multi-color LEDs; vibration Voice and AudioVoice and AudioThree microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support; Cellular circuit switch voice; HD VoicePERFORMANCE CHARACTERISTICSCPUTC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processorOperating SystemTC75: 1.6 B RAM / 8 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLCUSER ENVIRONMENTOperating Temp4° F to 152° F/-20° C to 50°CStorage Temp40° F to 158° F/-40° C to 70° CHumidity5% to 85% non-condensingDrop SpecificationMultiple 8 ft./2.4 m drop to concrete at room temperature parture pa	Imager Window	Corning Gorilla Glass
Power         PowerPrecision/PowerPrecision+*: Improved battery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-Ion 3.7 V, 4620 mAh typical; battery swap function           Expansion Slot         TC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC           SIM         TC75: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC           SIM         TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM (2FF)           Network Connections         USB 2.0 High Speed (host and client); WLAN           Notification         Audible tone; multi-color LEDs; vibration           Keypad         On-screen keypad; Enterprise Keyboard           Voice and Audio         Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support; Cellular circuit switch voice; HD Voice           PERFORMANCE CHARACTERISTICS         CPU           CPU         TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor           Operating System         IC75: 1.6 BRAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC           USER ENVIRONMENT         Operating Temp.           Operating Temp.         -4° F to 152° F/-20° C to 50°C           Storage Temp.         -40° F to 158° F/-40° C to 70° C           User Flash pSLC         S% to 85%	Touchpanel	or gloved fingertip input (conductive stylus sold
VectorVectorExpansion SlotTC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC TC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXCSIMTC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF)Network ConnectionsUSB 2.0 High Speed (host and client); WLANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad; Enterprise KeyboardVoice and AudioTr75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processorCPUTC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processorOperating SystemTC75: 1.6 BRAM / 8 GB Flash pSLC TC75x: Android 7.1 (Nougat) with MxMemoryTC75: GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLCUSER ENVIRONMENT-4° F to 152° F/-20° C to 50°CStorage Temp40° F to 158° F/-40° C to 70° CHumidity5% to 85% non-condensingDrop SpecificationMultiple 8 ft./2.4 m drop to concrete at room temperature per MIL-570 8106, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range	Backlight	LED backlight
and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXCSIMTC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM (2FF)Network ConnectionsUSB 2.0 High Speed (host and client); WLANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad; Enterprise KeyboardVoice and AudioThree microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD VoicePERFORMANCE CHARACTERISTICSCPUTC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processorOperating SystemTC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 	Power	battery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-Ion 3.7 V, 4620 mAh typical;
TC75x:2 Nano SIM slot (4FF); 1 Mini SIM (2FF)Network ConnectionsUSB 2.0 High Speed (host and client); WLANNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad; Enterprise KeyboardVoice and AudioThree microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD VoicePERFORMANCE CHARACTERISTICSCPUTC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processorOperating SystemTC75: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) 	Expansion Slot	and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC
ConnectionsNotificationAudible tone; multi-color LEDs; vibrationKeypadOn-screen keypad; Enterprise KeyboardVoice and AudioThree microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD VoicePERFORMANCE CHARACTERISTICSCPUTC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processorOperating SystemImage: TC75: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with MxMemoryTC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLCUSER ENVIRONMENTOperating Temp4° F to 122° F/-20° C to 50°CStorage Temp40° F to 158° F/-40° C to 70° CHumidity5% to 85% non-condensingDrop SpecificationMultiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature rangeTumble Specification2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	SIM	TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM (2FF)
Keypad       On-screen keypad; Enterprise Keyboard         Voice and Audio       Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice         PERFORMANCE CHARACTERISTICS         CPU       TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor         Operating System       Image: TC75: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx         Memory       TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC         USER ENVIRONMENT       Operating Temp.         -4° F to 122° F/-20° C to 50°C       -40° F to 158° F/-40° C to 70° C         Humidity       5% to 85% non-condensing         Drop Specification       Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range         Tumble Specification       2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC		USB 2.0 High Speed (host and client); WLAN
Voice and Audio       Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support; Cellular circuit switch voice; HD Voice         PERFORMANCE CHARACTERISTICS         CPU       TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor         Operating System       TC75: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx         Memory       TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC         USER ENVIRONMENT       Operating Temp.         -4° F to 122° F/-20° C to 50°C         Storage Temp.       -40° F to 158° F/-40° C to 70° C         Humidity       5% to 85% non-condensing         Drop Specification       Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range         Tumble Specification       2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Notification	Audible tone; multi-color LEDs; vibration
vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice         PERFORMANCE CHARACTERISTICS         CPU       TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor         Operating System       Image: Core of the core of	Keypad	On-screen keypad; Enterprise Keyboard
CPU       TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor         Operating System       TC75: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx         Memory       TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC         USER ENVIRONMENT         Operating Temp.       -4° F to 122° F/-20° C to 50°C         Storage Temp.       -40° F to 158° F/-40° C to 70° C         Humidity       5% to 85% non-condensing         Drop Specification       Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range         Tumble Specification       2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Voice and Audio	vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset
TC75x: 1.8 GHz hex core 64 bit processor         Operating System       TC75: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx         Memory       TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC         USER ENVIRONMENT         Operating Temp.       -4° F to 122° F/-20° C to 50°C         Storage Temp.       -40° F to 158° F/-40° C to 70° C         Humidity       5% to 85% non-condensing         Drop Specification       Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range         Tumble Specification       2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	PERFORMANCE	CHARACTERISTICS
Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx         Memory       TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC         USER ENVIRONMENT         Operating Temp.       -4° F to 122° F/-20° C to 50°C         Storage Temp.       -40° F to 158° F/-40° C to 70° C         Humidity       5% to 85% non-condensing         Drop Specification       Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range         Tumble Specification       2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	CPU	
TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC         USER ENVIRONMENT         Operating Temp.       -4° F to 122° F/-20° C to 50°C         Storage Temp.       -40° F to 158° F/-40° C to 70° C         Humidity       5% to 85% non-condensing         Drop Specification       Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range         Tumble Specification       2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Operating System	Mobility Extensions (Mx)
Operating Temp.       -4° F to 122° F/-20° C to 50°C         Storage Temp.       -40° F to 158° F/-40° C to 70° C         Humidity       5% to 85% non-condensing         Drop Specification       Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range         Tumble Specification       2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Memory	TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM /
Storage Temp.       -40° F to 158° F/-40° C to 70° C         Humidity       5% to 85% non-condensing         Drop Specification       Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range         Tumble Specification       2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	USER ENVIRONM	ENT
Humidity         5% to 85% non-condensing           Drop Specification         Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range           Tumble Specification         2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Operating Temp.	-4° F to 122° F/-20° C to 50°C
Drop Specification         Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range           Tumble Specification         2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Storage Temp.	-40° F to 158° F/-40° C to 70° C
temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range           Tumble Specification         2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Humidity	5% to 85% non-condensing
	Drop Specification	temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature
	Tumble Specification	

USER ENVIRONM	ENT (CONTINUED)
Sealing	IP65 and IP67 per applicable IEC sealing specifications
Vibration	4 g's PK Sine (5 Hz to 2 kHz); 0.04g2/Hz Random (20 Hz to 2 kHz); 60 minute duration per axis, 3 axis
Thermal Shock	-40° F to 158° F/-40° C to 70° C rapid transition
Electrostatic Discharge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge
INTERACTIVE SEI	NSOR TECHNOLOGY (IST)
Light Sensor	Automatically adjusts display backlight brightness
Motion Sensor	eCompass, 3-axis Gyro, 3-axis accelerometer
DATA CAPTURE	
Scanning	SE4750 imager (1D and 2D); extraordinary range: Scan range – Code 39 barcode: 20 Mil: 1.6 in to 36.3 in/4.1 cm to 92.2cm 3 Mil: 2.8 in to 6.2 in/7.1 cm to 15.9 cm
Camera	Rear – 8 MP autofocus; f/2.4 aperture (TC75) Rear – 13MP autofocus (TC75x) Front – 1.3 MP fixed focus (TC75/TC75x)
NFC	TC75: Type A and B, Felica and ISO 15693 cards. P2P mode and Card Emulation via UICC and Host TC75X: ISO 14443 Type A and B; Felica, and ISO 15693 cards. P2P mode and Card Emulation via UICC and Host
WIRELESS WAN D	ATA AND VOICE COMMUNICATIONS
Radio Frequency Band	TC75 Worldwide: LTE: 800/850/900/1800/2100/2600 (FDD 20,5,8,3,1,7); UMTS/HSPA/HSPA+: 850/900/1900/2100; GSM/GPRS/ EDGE: 850/900/1800/1900 Americas: LTE: 700/850/1900/AWS/2100 (FDD 17,5,2,4,1); UMTS/ HSPA/HSPA+: 850, 900, AWS, 1900, 2100; GSM/GPRS/ EDGE: 850/900/1800/1900
	TC75x Worldwide: LTE: 700,800/850/900/1800/2100/2600 (FDD 28,20,5,8,3,1,7); UMTS/HSPA/HSPA+: 850/900/1900/2100; GSM/GPRS/EDGE: 850/900/1800/1900 Americas: LTE: 700/850/1900/AWS/2100, (FDD 13,12,17,5,26,2,25,4,1); UMTS/HSPA/HSPA+: 850, 900, AWS, 1900, 2100 GSM/GPRS/EDGE: 850/900/1800/1900; CDMA: 850,1900 (BC0, BC10, BC1)
GPS	TC75: Integrated, Autonomous, Assisted GPS (A-GPS), Navstar, GLONASS TC75x: Integrated, Autonomous, Assisted GPS (A-GPS),

### **TC75 Series Specifications (continued)**

WIRELESS LAN		
Radio	TC75: IEEE® 802.11a/b/g/n/d/h/i/k/r TC75x: 2x2 MIMO; IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/w	
Data Rates	<b>TC75</b> 5GHz: 802.11a/n — up to 150 Mbps; 2.4GHz: 802.11b/g/n — up to 72.2 Mbps <b>TC75x</b> 5GHz: 802.11a/n/ac — up to 866.7 Mbps; 2.4GHz: 802.11b/g/n — up to 144 Mbps	
Operating Channels	TC75           Chan 1 - 13 (2412 - 2472 MHz); Chan 36 - 165           (5180 - 5825 MHz)           Channel Bandwidth: 20, 40 MHz           TC75x           Chan 1 - 13 (2412 - 2472 MHz), Chan 36 - 165 (5180 - 5825 MHz), Chan 138, Chan 142           Channel Bandwidth: 20, 40, 80 MHz           Actual operating channels/ frequencies depend on regulatory rules and certification agency	
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP and AES) — EAP- TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0- MSCHAPv2, PEAPv1-EAP-GTC, EAP Fast <sup>2</sup> and LEAP Data in Motion: FIPS 140-2 Level 1 Data at Rest: FIPS 140-2 Level 1	
Features	TC75: Wi-Fi Multimedia <sup>™</sup> (WMM), Soft AP, Wi-Fi Direct, Miracast TC75x: Wi-Fi Multimedia (WMM), Soft AP, MIMO with 2 Spatial Streams, 256 QAM Modulation on 5G GHz radio; Maximum Ratio Combining (MRC), Tx/Rx Low-Density Parity Check (LDPC), Transmit Beamforming(TXBF) and Beamformee (BFee) capability, Full IEEE 802.11 a/b/g/n legacy compatibility	
Certifications	TC75: WFA (802.11n, WMM-PS, Wi-Fi Direct, WPS, Miracast) TC75x: WFA (802.11n, 802.11ac, Mobile AP, Personal Hotspot, Miracast, WMM-PS, WMM-AC and Voice Enterprise)	
Fast Roam	PMKID caching, Cisco CCKM, 802.11r, OKC	

WIRELESS PAN	
Bluetooth	Class 2, Bluetooth v4.0 (Bluetooth® Smart technology) BT Wideband support HFPv1.6 Bluetooth v4.1 LE (TC75x only)
COMMUNICATION	AND MESSAGING
(PTT) small group Connect PTT Pro (suppor talk solution which also i radio integration. Workfo	ect PTT Express (included) provides instant push-to-tal o communications across Wi-Fi networks. Workforce rted) provides a scalable network agnostic push-to- includes messaging, location services and two-way orce Connect Voice client (supported) enables the as a full featured mobile telephone with multi-line letworks.
ADDITIONAL MOB	BILITY DNA SOLUTIONS
computers by a and manageme	olutions help you get more value out of our mobile udding functionality as well as simplifying deployment ent of our mobile devices. For more information on these tures, please visit www.zebra.com/mobilitydna yboard Enterprise Home Screen
Stage Now	AppGallery
EMDK	Enterprise Browser
SimulScan	
Available Mobility DNA fe	
	eatures may vary by model.
WARRANTY	eatures may vary by model.
Subject to the terms of Z is warranted against def	ebra's hardware warranty statement, the TC75 Series fects in workmanship and materials for a period of 1 of shipment. For complete warranty statement, pleas
Subject to the terms of Z is warranted against def (one) year from the date	lebra's hardware warranty statement, the TC75 Series fects in workmanship and materials for a period of 1 of shipment. For complete warranty statement, please com/warranty

1. PowerPrecision+ batteries are available only on TC75x models and provide advanced state of health and advanced state of charge metrics.

2. EAP Fast supported on TC75 models only.

Specifications subject to change without notice and some features may vary by model.



reddot award 2016 winner industrial design







Asia-Pacific Headquarters +65 6858 0722 contact.apac@zebra.com EMEA Headquarters zebra.com/locations contact.emea@zebra.com

÷

android

enterprise recommended

> Latin America Headquarters +1 847 955 2283 la.contactme@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. Part number: SS-TC75 08/28/2018