




# VASARIO SERIES

## PRODUCT SPECIFICATIONS



### ELECTRONICALLY OPERATED (Media)

#### 1915 MODEL




**Dimensions:**  
(width x depth x height)  
Height without feet:

18.8 x 15.2 x 4.3 inches  
478 x 386 x 110 mm  
3.8 inches or 97 mm

**Shipping weight:**  
22 lbs  
10 kg

#### 1618 MODEL




**Dimensions:**  
(width x depth x height)  
Height without feet:

16.2 x 18.3 x 4.3 inches  
411 x 466 x 110 mm  
3.8 inches or 97 mm

**Shipping weight:**  
21 lbs  
9.5 kg

#### 1616 MODEL




**Dimensions**  
(width x depth x height)  
Height without feet

16.2 x 16.3 x 4.3 inches  
411 x 415 x 110 mm  
3.8 inches or 97 mm

**Shipping weight**  
19 lbs  
8.6 kg

#### 1313 MODEL




**Dimensions**  
(width x depth x height)  
Height without feet

13.1 x 13.1 x 3.93 inches  
335 x 335 x 100 mm  
3.6 inches or 91 mm

**Shipping weight**  
13 lbs  
5.9 kg

### ELECTRONICALLY OPERATED (Non-Media)

#### 1416 MODEL




**Dimensions**  
(width x depth x height)  
Height without feet

13.8 x 16.3 x 4.0 inches  
351 x 415 x 102 mm  
3.5 inches or 89 mm

**Shipping weight**  
16 lbs  
7.3 kg

### MANUALLY OPERATED (Non-Media)

#### 1616 MODEL




**Dimensions**  
(width x depth x height)  
Height without feet

16.2 x 16.3 x 4.3 inches  
411 x 415 x 110 mm  
3.8 inches or 97 mm

**Shipping weight**  
19 lbs  
8.6 kg

# MANUALLY OPERATED (Non-Media) Continued

## 1416 MODEL



**Dimensions**  
(width x depth x height)  
Height without feet

13.8 x 16.3 x 4.0 inches  
351 x 415 x 102 mm  
3.5 inches or 89 mm

**Shipping weight** 16 lbs  
7.3 kg

## FEATURES

- Numerous till configurations available. See our **Standard Duty Accessories brochure** or contact your APG representative for options
- Electronic drawers tested to last beyond one million operations
- Manual drawers tested to last to 300,000 operations
- Under till storage area
- Lower cost solution provides value in lower traffic retail environments
- Available in Black, White and Beige, with either a painted or stainless steel drawer front (stainless not available for manually operated drawers)
- Four function lock
- Closed and latched drawer status switch (not available in manual)
- Random keying is standard, other lock and key options available

## AVAILABLE INTERFACES

101	Manually Operated Drawer**	554A	USBPro™ II, USB Interface
320	MultiPRO® 24 volt *	484A	SerialPRO® II
420	MultiPRO® II 12 volt *	XXX	Other interface numbers indicate a custom interface

\* Requires detachable cable sold separately. Refer to Connectivity Guide at [www.cashdrawer.com](http://www.cashdrawer.com) for interface cable detail.

\*\* Only available for the 1416 and 1616 models

## OPERATING ENVIRONMENT

<b>Storage Temperature</b>	-30°C to +50°C (-22°F to +122°F)	<b>Relative Humidity</b>	10% to 95%
<b>Operating Temperature</b>	0°C to +40°C (+32°F to +104°F)	<b>(non-condensing)</b>	

## ACCESSORIES

See our **Standard Duty Accessories brochure** or contact your APG representative for options

1. Tills
2. Locking till covers
3. Weighable coin cups
4. Under counter mounting brackets

## WARRANTY

**Two (2) year limited warranty.** A full warranty statement is available online at [www.cashdrawer.com/support/warranty-statement](http://www.cashdrawer.com/support/warranty-statement).



APG Cash Drawer, LLC  
5250 Industrial Blvd. N.E.  
Minneapolis, MN 55421

Phone: 763 571 5000  
Fax: 763 571 5771

APG® Cash Drawer, the APG Cash Drawer logo, SerialPRO®, MultiPRO®, DirectPRO®, USBPro™, ParallelPRO™, POS-Integrator™, Vasario™, POS-Podium™ and Cash Drawer Caddy™ are trademarks of APG Cash Drawer, LLC.

M-43-111 Rev. D